

TIREMAAX® TIRE INFLATION SYSTEM

This unit is equipped with the TIREMAAX® tire inflation system.

If the lamp remains on continuously for more than 10 minutes, one or more tires may be low or the system requires service.

In the event of a substantial system leak, set the trailer park brakes, then close controller supply valve.

For complete service details, refer to Hendrickson publication T51002, TIREMAAX Installation, Service and Troubleshooting Procedures, or call the Hendrickson Technical Services Department in the United States at 866-RIDEAIR (743-3247) or in Canada at 800-668-5360.

Trailer Commercial Vehicle Systems
2070 Industrial Place SE
Canton, OH 44707-2641 USA
866.RIDEAIR (743.3247)
330.489.0045
FAX 800.696.4416



www.hendrickson-intl.com

Trailer Commercial Vehicle Systems
250 Chrysler Drive, Unit #3
Brampton, OH Canada L6S 6B6
905.789.1030
FAX 905.789.1033

T50014 08-11 ECN 20041

©2011 Hendrickson USA, L.L.C. (U.S. Rights) Hendrickson Intl Corp (Rights Outside U.S.) All Rights Reserved

Printed in the United States of America

DECAL SPECIFICATIONS

The type of material and adhesive used to produce and apply a decal is determined by the printer according to Table 1 (Table 18 of Hendrickson Trailer Division Technical Literature Style Guide). Decal specifications must be included with the decal file sent to print according to the Trailer Division Technical Literature Style Guide.

SIZE: 7 in W x 4.5 in H

Special Instructions: This decal is packaged with the TIREMAAX® TIS and applied by the OE. It is valid for TIREMAAX CP & PRO systems available after June 2011.

Width Constraint ¹	Height Constraint ¹	Exposure to Sunlight ²	Water Resistant ³	Water Proof ⁴	Special Adhesive ⁵	Paint Mask ⁶	Heat ⁷	Cold ⁸	Extreme Wind ⁹	Writable ¹⁰
		X	X							

- Relative to intended location, maximum or minimum size constraints must apply as listed. None if left blank.
- Must not fade when exposed to sunlight over life of decal.
- Be able to resist rain water and hold position. Usually mounted vertically or at an incline such that water easily runs off.
- Able to hold position and not degrade when submerged or hold standing water.
- A special adhesive applies to surfaces where decals have difficulty sticking to. X = default values specified in [Table 2](#).
- Covered with a removable mask. The mask should include a pull tab for ease of removal after painting.
- Remain in tact and not fade or degrade in hot temperatures.
- Hold position at low temperatures.
- An example of this would be a hubcap decal that is exposed to spinning and exposure to the wind and any particles carried within it.
- Must be able to write on decal with permanent marker or ball point pen.

Table 1 : *Hendrickson approved decal adhesives*

ADHESIVES

The following are preferred adhesives for Hendrickson Trailer decals. They have been tested with favorable results in Hendrickson Trailer applications. Hendrickson must be contacted prior to using other adhesive types.

Property	Primary	Alternative
	Fasson® TL2	P1480
Manufacture	Fasson	3M
Manufacture web site	www.na.fasson.com	www.3m.com
Adhesive type	Hot melt rubber	High performance tackified acrylic
Minimum application temperature	35° F (2° C)	40° F to 120° F (5° C to 49° C)
Service temperature range	-65° F to 150° F (-54° C to 65.5° C)	-20° F to 140° F (-29° C to 60° C)

Table 2: *Hendrickson approved decal adhesives*