

HT250YS Y-BEAM SPECIFICATIONS

LIT NO: L1186 **DATE**: April 2011





APPLICATIONS

| CAPACITY*: | HT250YS - 25,000 lbs. (11 300 kg) | | | | |
|-------------------|---|--|--|--|--|
| TRAILER TYPES: | U.S.A. and Canada: Lowboy / Drop Deck, Specialty Trailers | | | | |
| | Mexico, Central and South America: None | | | | |
| AXLE DATA: | 5-inch diameter round, 5/8-inch wall, S-cam, w/ or w/o auto slack adjusters for 15-, 20-, or 22-inch wheels | | | | |
| | Brake size: 12.25 or 16.50 inch | | | | |
| AXLE ARRANGEMENT: | Single, tandem: 122-inch maximum axle spacing | | | | |
| | Tri or quad: 144-inch maximum total spacing | | | | |
| FRAME TYPES: | Steel; 96-inch or 102-inch wide trailers | | | | |

^{*} Capacity refers to the suspension ratings. Ratings for the axle, brakes and wheel-end components differ depending upon their specifications

SPECIFICATIONS

| Suspension Model Number | Ride Height (inches) | Jounce (inches) | Rebound (inches) | Weight (lbs.) ¹ | Compatible Trailing Suspension |
|----------------------------|-------------------------|--------------------|---------------------|-------------------------------|---|
| HT250YS ² | 6.5 | 3.3 | 4.0 | 338 | HT250US with Compatible Specs ³ |
| | 7.5 | 3.9 | 4.0 | 338 | |
| | 9 | 4.7 | 4.0 | 338 | |

All models for the HT250YS feature the QUIK-ALIGN® pivot connection.

Options available for HT250YS

High pressure air springs Rotated air spring Shock straps⁴

- 1. Weights shown above are for standard models (standard air spring and shock) and do not include axle
- 2. Model number varies depending on options selected
- 3. Consult Hendrickson to verify suspension comparability
- 4. Shock strap kit must be ordered separately from suspension contact Hendrickson for proper kit

SUSPENSION APPLICATION NOTE:

Care must be taken to insure that any additional suspensions used on the same vehicle are compatible with the Y-beam suspension. For assistance, please contact your Hendrickson Trailer Suspension Systems customer service representative.

www.hendrickson-intl.com



Trailer Suspension Systems 250 Chrysler Drive, Unit #3 Brampton, ON Canada L6S 6B6 905.789.1030 Fax 905.789.1033 Trailer Suspension Systems 2070 Industrial Place SE Canton, OH 44707-2641 USA 866.RIDEAIR (743.3247) 330.489.0045 Fax 800.696.4416 Hendrickson Mexicana Av. Industria Automotriz #200 Parque Industrial Stiva Aeropuerto Apodaca, N.L., México C.P. 66600 +52 (81) 8288.1300 Fax +52 (81) 8288.1301