

HENDRICKSON USE ONLY

H ORDERING GUIDE

INTRAAX® SUSPENSION

LIT NO: L602

DATE: April 2012

REVISION: Q

FORM INSTRUCTIONS:

For complete price and model number information on an INTRAAX® suspension system, fax this form to 800.696.4416 in the U.S. or 905.789.1033 in Canada. For additional assistance, please call toll-free 866.RIDEAIR (743.3247) in the U.S. or 800.668.5360 in Canada.

TO: _____ **FROM:** _____ **COMPANY NAME:** _____
DATE: _____ **PHONE:** _____ **FAX:** _____

SAME AS: _____ **EXCEPT:** _____

SUSPENSION

SUSPENSION MODEL:	<input type="checkbox"/> AANT 23K	<input type="checkbox"/> AAT 23K	<input type="checkbox"/> AAT 25K	<input type="checkbox"/> AAT 30K ¹	<input type="checkbox"/> AAEDT 30K			
	<input type="checkbox"/> AANLS 20K	<input type="checkbox"/> AANL 23K	<input type="checkbox"/> AAL 23K	<input type="checkbox"/> AAL 25K	<input type="checkbox"/> AAL 30K ¹	<input type="checkbox"/> AAEDL 30K		
RISE HEIGHT: (Inches)	<input type="checkbox"/> 6.25	<input type="checkbox"/> 6.5	<input type="checkbox"/> 7	<input type="checkbox"/> 7.5	<input type="checkbox"/> 8	<input type="checkbox"/> 9	<input type="checkbox"/> 12	<input type="checkbox"/> 13
	<input type="checkbox"/> 13.5	<input type="checkbox"/> 14	<input type="checkbox"/> 15	<input type="checkbox"/> 16	<input type="checkbox"/> 17	<input type="checkbox"/> 18	<input type="checkbox"/> 19	
FRAME BRACKET:	<input type="checkbox"/> Bolt-On	<input type="checkbox"/> Weldable Bolt-On	<input type="checkbox"/> Side-Mount Bolt-On		<input type="checkbox"/> Weld-On	<input type="checkbox"/> Other:		
	MOUNTING BOLT SIZE:		<input type="checkbox"/> 0.500"	<input type="checkbox"/> 0.625"	BOLT PATTERN NUMBER:			
FRAME BRACKET STYLE:	<input type="checkbox"/> Wingless Hanger		<input type="checkbox"/> Hanger with Wing					
FRAME BRACKET PROFILE:	<input type="checkbox"/> N/A	<input type="checkbox"/> Standard	<input type="checkbox"/> Tapered (AANT/AANL models only ²)					
FRONT SHOCK ABSORBER:	<input type="checkbox"/> Standard	<input type="checkbox"/> Extended Service/High Damping			<input type="checkbox"/> No ³			
FRONT SHOCK STRAPS:	<input type="checkbox"/> Yes	<input type="checkbox"/> No						
REAR SHOCK ABSORBER⁴:	<input type="checkbox"/> Extended Service/High Damping			<input type="checkbox"/> No				
REBOUND LIMITER:	<input type="checkbox"/> Yes	<input type="checkbox"/> No						
SURELOK® READY:	<input type="checkbox"/> Yes	<input type="checkbox"/> No						
TRAVEL:	<input type="checkbox"/> Standard	<input type="checkbox"/> Ltd Jounce/Up-Travel (AAL)		<input type="checkbox"/> Ltd Rebound/Down-Travel (AAT)				

1. Suspension models are limited to a 25,000-pound axle rating.

2. Frame bracket profile is required for all AANT models and 12- through 17-inch rise height AANL models.

3. Selection only permitted when rear shock absorbers are specified.

4. Rear shock absorbers are available on AAL, AAEDT and AAEDL suspensions only.

H HENDRICKSON

SUSPENSION (CONTINUED)

AIR SPRING PSI RANGE:	<input type="checkbox"/> Standard	<input type="checkbox"/> Low Pressure (Limited Availability by Model)			
HIGH CONTROL SUSPENSION ⁵:	<input type="checkbox"/> Yes	<input type="checkbox"/> No			
CHANNEL:	<input type="checkbox"/> Standard C-Channel	<input type="checkbox"/> Bolt-on C-Channel with Struts ⁶	<input type="checkbox"/> Customer Supplied	<input type="checkbox"/> Included	<input type="checkbox"/> Other:
BUSHING TUBE SPACER^{7,8}:	<input type="checkbox"/> Standard	<input type="checkbox"/> Optional Cap Style			
FRAME BRACKET TO BEAM:	<input type="checkbox"/> Assembled	<input type="checkbox"/> Non-Assembled			
SUSPENSION PAINT OPTIONS:					
Surface Coating — Axle/Beam Weldment:	<input type="checkbox"/> None	<input type="checkbox"/> Standard Black Primer	<input type="checkbox"/> Finished Soft Coat- Black	<input type="checkbox"/> Finished Soft Coat- Gray	
Surface Coverage — Frame Brackets:	<input type="checkbox"/> Standard (same as surface coating)	<input type="checkbox"/> None /Do Not Paint Frame Brackets	<input type="checkbox"/> Galvanized ⁹		

A X L E * (*Refer to "L846 – Wide Base Tire Configuration Bulletin" for Track / Wheel Recommendations)

STYLE:	<input type="checkbox"/> Straight	<input type="checkbox"/> Cambered (AANT, AAT)	<input type="checkbox"/> Raised Center (AAT 23K & 25K Only)				
TRACK (Inches):	<input type="checkbox"/> 71.5	<input type="checkbox"/> 73	<input type="checkbox"/> 75.5	<input type="checkbox"/> 76.5	<input type="checkbox"/> 77.5	<input type="checkbox"/> 83.5	<input type="checkbox"/> 85
SPINDLE:	<input type="checkbox"/> HN	<input type="checkbox"/> HP					
AXLE WALL:	<input type="checkbox"/> Standard	<input type="checkbox"/> Heavy Duty (Limited Availability by Model)					
TIRE INFLATION SYSTEM ¹⁰:	<input type="checkbox"/> No	<input type="checkbox"/> TIREMAAX [®] CP Integrated (Complete Worksheet on p. 4)		<input type="checkbox"/> TIREMAAX [®] PRO (Complete Worksheet on p. 4)		<input type="checkbox"/> 3-Hole Prep	

B R A K E S

BRAKE TYPE:	<input type="checkbox"/> Drum	<input type="checkbox"/> Air Disc (Complete "L895 – Air Disc Brake Ordering Guide")				
BRAKE SIZE:	<input type="checkbox"/> 16.5" x 7"	<input type="checkbox"/> 16.5" x 7" HXS [®]	<input type="checkbox"/> 16.5" x 8-5/8" HXS	<input type="checkbox"/> 15" x 8-5/8" HXS (Not available on product w/ LDA)		
BRAKE SHOE/LINING:	<input type="checkbox"/> Abex 3030-197	<input type="checkbox"/> Abex 931-162	<input type="checkbox"/> Hendrickson ULTRAA 20™		<input type="checkbox"/> Abex NAB 456	
S-CAM:	<input type="checkbox"/> 28 Spline	<input type="checkbox"/> 10 Spline				
BRAKE CHAMBER:	<input type="checkbox"/> No	<input type="checkbox"/> Standard 30/30, 2.5" Stroke				
BRAKE CHAMBER WARRANTY:	<input type="checkbox"/> No	<input type="checkbox"/> Standard (4-Year Limited)	<input type="checkbox"/> Extended Life (6-Year Limited)			
BRAKE ADJUSTER:	<input type="checkbox"/> No	<input type="checkbox"/> Standard 5.5"	<input type="checkbox"/> Standard 6.0"			
DUST SHIELD:	<input type="checkbox"/> No	<input type="checkbox"/> Yes				
ABS SENSOR:	<input type="checkbox"/> No	<input type="checkbox"/> Haldex 19.7"	<input type="checkbox"/> Wabco 15.7"			
SPINDLE NUT:	<input type="checkbox"/> No	<input type="checkbox"/> Standard 3-Piece Nut				

5. High control suspensions are recommended for single-axle trailers in multi-trailer combinations, all dollies and full trailers with two single axles. Not for use on multiple-axle trailers.
6. Only available with bolt-on frame brackets.
7. The cap style bushing tube spacer is a standard component on the following models: AAEDT / AAEDL 30K, AAT / AAL 30K. It is an available option on: AAT / AAL 23K, AAT / AAL 25K. It is not available on AANLS 20K, AANL 23K or AANT 23K suspensions.
8. All logging trailers and petroleum tankers require the cap style bushing tube spacer.
9. Galvanized coating option is only available with bolt-on frame brackets and is not compatible with weld-on channels or other weld-on components assembled by the OEM.
10. Hendrickson does not provide warranty coverage for the installation, performance or components of a competitor brand tire inflation system installed on a Hendrickson suspension. Any consequential damages to the Hendrickson suspension resulting from a failure to the competitor brand tire inflation system or components, whether installed by the OEM, repair facility or end-user customer, should be directed to the respective tire inflation system manufacturer for warranty coverage.

	<input type="checkbox"/> Standard Service (1-Year Limited Warranty ¹²)	<input type="checkbox"/> Hendrickson Value System™ – HVS® (3-Year Limited Warranty ¹²)	<input type="checkbox"/> Hendrickson Long-Life System™ – HLS® (5-Year Limited Warranty ¹²)	<input type="checkbox"/> Hendrickson Extended Life System™ – HXL7® (7-Year Limited Warranty ¹²)	<input type="checkbox"/> ConMet PreSet® (5-Year Limited Warranty ¹²)
SPINDLE:	<input type="checkbox"/> HN <input type="checkbox"/> HP	<input type="checkbox"/> HN <input type="checkbox"/> HP	<input type="checkbox"/> HN <input type="checkbox"/> HP	HP	<input type="checkbox"/> HN <input type="checkbox"/> HP
HUB MATERIAL:	<input type="checkbox"/> Ductile Iron <input type="checkbox"/> Dura-Light Hubs® <input type="checkbox"/> Aluminum	<input type="checkbox"/> Ductile Iron <input type="checkbox"/> Dura-Light Hubs <input type="checkbox"/> Aluminum	<input type="checkbox"/> Ductile Iron <input type="checkbox"/> Dura-Light Hubs <input type="checkbox"/> Aluminum	<input type="checkbox"/> Ductile Iron <input type="checkbox"/> Aluminum	Aluminum
HUB STYLE:	Hub Piloted	Hub Piloted	Hub Piloted	Hub Piloted	Hub Piloted
NUMBER OF STUDS:	10	10	10	10	10
BOLT CIRCLE DIAMETER:	11.25"	11.25"	11.25"	11.25"	11.25"
WHEEL MATERIAL¹³:	<input type="checkbox"/> Aluminum <input type="checkbox"/> Steel <input type="checkbox"/> Steel / Aluminum	<input type="checkbox"/> Aluminum <input type="checkbox"/> Steel <input type="checkbox"/> Steel / Aluminum	<input type="checkbox"/> Aluminum <input type="checkbox"/> Steel <input type="checkbox"/> Steel / Aluminum	<input type="checkbox"/> Aluminum <input type="checkbox"/> Steel <input type="checkbox"/> Steel / Aluminum	<input type="checkbox"/> Aluminum <input type="checkbox"/> Steel <input type="checkbox"/> Steel / Aluminum
DUAL / SUPER SINGLE¹³: (SS) Short Stud (LS) Long Stud	<input type="checkbox"/> Dual <input type="checkbox"/> Super Single (SS) <input type="checkbox"/> Super Single (LS)	<input type="checkbox"/> Dual <input type="checkbox"/> Super Single (SS) <input type="checkbox"/> Super Single (LS)	<input type="checkbox"/> Dual <input type="checkbox"/> Super Single (SS) <input type="checkbox"/> Super Single (LS)	<input type="checkbox"/> Dual <input type="checkbox"/> Super Single (SS) <input type="checkbox"/> Super Single (LS)	<input type="checkbox"/> Dual <input type="checkbox"/> Super Single (SS) <input type="checkbox"/> Super Single (LS)
DRUM MATERIAL¹³:	<input type="checkbox"/> Cast <input type="checkbox"/> Fused	<input type="checkbox"/> Cast <input type="checkbox"/> Fused	<input type="checkbox"/> Cast <input type="checkbox"/> Fused	<input type="checkbox"/> Cast <input type="checkbox"/> Fused	<input type="checkbox"/> Cast <input type="checkbox"/> Fused
LUBE TYPE:	<input type="checkbox"/> SAE 80/90 <input type="checkbox"/> Semi-Fluid Grease <input type="checkbox"/> Synthetic 75W/90	<input type="checkbox"/> SAE 80/90 <input type="checkbox"/> Synthetic 75W/90	Semi-Fluid Grease	Semi-Fluid Grease	<input type="checkbox"/> Semi-Fluid Grease <input type="checkbox"/> Synthetic 75W/90
SEAL:	<input type="checkbox"/> Stemco Voyager (Standard) <input type="checkbox"/> Stemco Discover <input type="checkbox"/> Stemco Guardian <input type="checkbox"/> Federal Mogul	Standard	Standard	Standard	No (ConMet Included)
BEARING:	Standard	Standard	Standard	Standard	No (ConMet Included)
SPINDLE NUT:	Standard 3-Piece Nut	Standard 3-Piece Nut	Standard 3-Piece Nut	Precision320™ Nut System	Standard 3-Piece Nut
HUBCAP TYPE:	Standard Bolt-on	Standard Bolt-on	Standard Bolt-on	Corrosion Resistant Bolt-on	Standard Bolt-on
ABS TONE RING:	Yes	Yes	Yes	Yes	Yes

DRUM OPTIONS

DRUM DUTY:	<input type="checkbox"/> Standard	<input type="checkbox"/> Heavy Duty
DRUM BALANCING:	Balanced	
WHEEL FASTENERS:	<input type="checkbox"/> Yes ¹⁴	<input type="checkbox"/> No

11. Consult a customer service representative to ensure the compatibility of the wheel-end equipment with the other selected suspension parameters.

12. Refer to Hendrickson publication "L583 – Comprehensive Warranty Statement" for complete details.

13. Information purpose only, not for ordering. Contact Hendrickson for the axle rating when offset wheels are used.

14. Two (2) wheel fasteners factory installed per wheel-end with balance packaged in plastic bag, taped and stretch-wrapped to each wheel-end.

ACCESSORY ITEMS (Not Included in INTRAAX® Model Number — Sold Separately)

HEIGHT CONTROL VALVE:	<input type="checkbox"/> Yes <input type="checkbox"/> No	Integral Dump:	<input type="checkbox"/> Yes <input type="checkbox"/> No
MANUAL DUMP VALVE:	<input type="checkbox"/> Yes <input type="checkbox"/> No	With Enclosure:	<input type="checkbox"/> Yes <input type="checkbox"/> No
UNIVERSAL LOAD SCALE KIT:	<input type="checkbox"/> Yes <input type="checkbox"/> No		
UNDER BEAM LIFT™(UBL™)¹⁵:	<input type="checkbox"/> Yes <input type="checkbox"/> No		

TIREMAAX® KIT WORKSHEET¹⁶ (Not Included in INTRAAX Model Number — Sold Separately)

CONTROLLER TYPE:	<input type="checkbox"/> CP Integrated <input type="checkbox"/> PRO
NUMBER OF AXLES:	<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4 <input type="checkbox"/> Other:
HUBCAP TYPE:	<input type="checkbox"/> Hendrickson Bolt-On <input type="checkbox"/> Hendrickson Extended Bolt-On ¹⁷
LUBE TYPE:	<input type="checkbox"/> Semi-Fluid Grease <input type="checkbox"/> Oil
WHEEL STYLE:	<input type="checkbox"/> Dual <input type="checkbox"/> Super Single - Steel 180° Fitting <input type="checkbox"/> Super Single - Steel 135° Fitting <input type="checkbox"/> Super Single - Aluminum Standard Fitting
TIRE SIZE:	<input type="checkbox"/> 17 - 19.5" <input type="checkbox"/> 22.5" <input type="checkbox"/> 24.5"
COLD TIRE PRESSURE SETTING (psi)¹⁸:	<input type="checkbox"/> 70 <input type="checkbox"/> 75 <input type="checkbox"/> 80 <input type="checkbox"/> 85 <input type="checkbox"/> 90 <input type="checkbox"/> 95 <input type="checkbox"/> 100 <input type="checkbox"/> 105 <input type="checkbox"/> 110 <input type="checkbox"/> 115 <input type="checkbox"/> 120
TRAILER-MOUNTED INDICATOR LAMP KIT:	<input type="checkbox"/> Standard <input type="checkbox"/> LED <input type="checkbox"/> No
WIRING HARNESS:	<input type="checkbox"/> Premium, 15-Foot, ABS-ready <input type="checkbox"/> Standard, 18-inch, Wiring Adaptor Plug <input type="checkbox"/> Premium, 3-Foot, ABS-ready
AIR PLUMBING KIT:	<input type="checkbox"/> Manifold ¹⁹ <input type="checkbox"/> None
CONTROLLER TANK VALVE²⁰: (Pressure Check)	<input type="checkbox"/> Yes <input type="checkbox"/> No

15. When selecting a UBL, its operating limitations may vary depending upon the suspension model, ride height and application. In some cases, a lift is only recommended for lifting an unloaded trailer. Contact Hendrickson for assistance.
16. When installing TIREMAAX, please contact Hendrickson to verify correct wheel-end component integration.
17. Required with TIREMAAX CP Integrated or TIREMAAX PRO equipped with castellated spindle nut. For axles equipped with cross-drilled spindles. Please verify spindle nut requirements. (Reference T57001)
18. Refer to tire manufacturer's recommended tire pressure. TIREMAAX PRO with Dual wheels restricted to Cold Tire Pressure Setting of 80-120 psi. TIREMAAX PRO with Single wheels restricted to Cold Tire Pressure Setting of 90-120 psi.
19. Not required for single-axle systems.
20. Not available with TIREMAAX PRO.



Hendrickson Canada
250 Chrysler Drive, Unit #3
Brampton, ON Canada L6S 6B6
905.789.1030
Fax 905.789.1033

Trailer Commercial Vehicle Systems 866.RIDEAIR (743.3247)
2070 Industrial Place SE 330.489.0045
Canton, OH 44707-2641 USA Fax 800.696.4416

Hendrickson Mexicana
Av. Industria Automotriz #200
Parque Industrial Sliva Aeropuerto
Apodaca, N.L., México C.P. 66600
+52 (81) 8288.1300
Fax +52 (81) 8288.1301