

INTRAAAX® AANT 23K

Narrow-bushing and tapered-beam technology makes the AANT 23K the premier top-mount system for weight-conscious haulers

Hendrickson trimmed an average of 50 pounds from an integrated suspension-axle-brake system already known throughout the industry for its lightweight and reliable performance. The INTRAAX® AANT 23K, standard with the Large-Diameter Axle (LDA™), allows you to move even more cargo on each haul.

Weighing in at 490 pounds for a standard configuration, the AANT 23K is the optimum system for weight-conscious haulers running straight-frame platforms, container chassis, liquid tankers, grain hoppers, bottom dumps and livestock trailers. The INTRAAX AANT boasts a capacity of 23,000 pounds in ride heights from 12 to 17 inches.



Even though we shaved its weight, the INTRAAX AANT maintains the same smooth ride, superior performance and rugged durability you need to protect your cargo and keep your equipment operating at peak performance mile after mile.

AANT teams tapered-beam and Hendrickson Large-Diameter Axle (LDA) technologies for increased stiffness, reduced weight and improved durability.

We adapted this tapered beam technology from our road-proven VANTRAAX® HKANT 40K slider system. With tens of thousands of units on the road today, VANTRAAX has grown to be the first choice of van operators.

To move more cargo with every load, ask your trailer dealer or a Hendrickson sales representative about the benefits of INTRAAX AANT.

For additional information, call **1-866-RIDEAIR** or visit our web site at www.hendrickson-intl.com.

 **HENDRICKSON**
The World Rides On Us™

INTRAAX® Benefits

• **Low maintenance**

- Proven TRI-FUNCTIONAL® Bushing technology for long life and a smooth ride
- QUIK-ALIGN® for fast, reliable and convenient axle alignment
- Rigid trailing arm and solid axle connection provides enhanced stability and dependable design
- Single source for technical support, training and warranty



• **Superior axle**

- Neutral-toe axle helps stretch mileage and tire life
- Patented axle wrap for optimal structural integrity
- Standard with the Hendrickson Large-Diameter Axle (LDA™)
- ✓ Increased bending stiffness by 14 percent over standard five-inch axles
- ✓ More bending stiffness means less axle deflection under load
- ✓ Available cambered axle option for grain and livestock trailers



• **Responsive, consistent braking power**

- Industry's first standard Cam Tube System™ to help extend brake component life
- Up to a half-inch less stroke required
- Available with air disc brakes



• **Wide range of READY-TO-ROLL® (RTR®) wheel-end options**

- **Hendrickson Value System™ (HVS™)** features a three-year limited on-highway warranty*
- **Hendrickson Long-Life System™ (HLS™)** features a five-year limited on-highway warranty*
- **Hendrickson Extended-Life 7-year System (HXL7™)** features a seven-year limited on-highway warranty*

**Contact your local Hendrickson representative for complete warranty terms, conditions and limitations*



HVS™ System



HLS™ System



HXL7™ System

AANT 23K Advantages

• **Installation efficiencies**

- Narrow hanger allows installation on trailer frame flanges as narrow as four inches — offering the potential for even greater weight savings
- Various frame mounting configurations provide flexibility
 - ✓ Tapered or straight profile, winged or wingless weld-on frame brackets — allow for installation directly and completely under the trailer main beams
 - ✓ Winged, bolt-on frame brackets — designed using a top-mount, bolt-on plate for aluminum frame trailers — also available with an optional galvanized coating that provides high-quality chip and corrosion resistance
 - ✓ Winged or wingless, side-mount, bolt-on frame brackets — designed for maximum clearance between frame brackets, mainly for livestock, tanker and grain hopper applications — also available with an optional galvanized coating that provides high-quality chip and corrosion resistance

• **Liftable**

- Combine your AANT system with an UNDER BEAM LIFT™ (UBL™) for cost savings and operational flexibility
 - ✓ Minimal maintenance required
 - ✓ Compact, lightweight design with few moving parts
 - ✓ No chains, cables or metal-on-metal parts to wear or bind

Actual product performance may vary depending upon vehicle configuration, operation, service and other factors.

Call your trailer dealer or Hendrickson at **1-866-RIDEAIR (743-3247)** for additional information.

www.hendrickson-intl.com



Trailer Suspension Systems
250 Chrysler Drive, Unit #3
Brampton, ON Canada L6S 6B6
905.789.1030
Fax 905.789.1033

Trailer Suspension Systems
2070 Industrial Place SE
Canton, OH 44707-2641 USA

866.RIDEAIR (743.3247)
330.489.0045
Fax 800.696.4416

Hendrickson Mexicana
Av. Industria Automotriz #200
Parque Industrial Sliva Aeropuerto
Apodaca, N.L., México C.P. 66600
+52 (81) 8288.1300
Fax +52 (81) 8288.1301