

HHT™ SERIES

HT190T SPECIFICATIONS

LIT NO: L111

DATE: June 2007

REVISION: C





APPLICATIONS

CAPACITY:	20,000 lbs. (9 000 kg)	
TRAILER TYPES:	UNITED STATES AND CANADA Van Reefer Container Chassis	MEXICO, CENTRAL AND SOUTH AMERICA None
AXLE DATA:	5-inch diameter round, 5/8-inch wall, 15- and 16.5-inch brakes	
AXLE ARRANGEMENT:	Single; tandem: 54-inch maximum axle spacing	
FRAME TYPES:	Steel only; 96-inch or 102-inch wide trailers	

MODEL CHART

SUSPENSION MODEL NUMBER ¹	RIDE HEIGHT (inches)	JOUNCE (inches)	REBOUND (inches)	WEIGHT ² (pounds)
HT190T-14-005	14	2.9	4.4	292
HT190T-15-005	15	3.3	4.4	294
HT190T-16-005	16	3.2	4.2	306
HT190T-17-005	17	3.3	4.4	309

¹Other models and options are available.

²Weights shown do not include the axle.

NOTE:

- HT190T models feature wingless style frame brackets with welded pivot connection.
- HT190TA models feature winged style frame brackets with QUIK-ALIGN® pivot connection.
- HT190TB models feature wingless style frame brackets with QUIK-ALIGN pivot connection.

www.hendrickson-intl.com



Trailer Suspension Systems
250 Chrysler Drive, Unit #3
Brampton, ON Canada L6S 6B6
905.789.1030
Fax 905.789.1033

Trailer Suspension Systems 866.RIDEAIR (743.3247)
2070 Industrial Place SE 330.489.0045
Canton, OH 44707-2641 USA Fax 800.696.4416

Trailer Suspension Systems
Ave. Industria Automotriz #200
Parque Industrial Silva Aeropuerto
Apodaca, N.L., México C.P. 66600
(52) 81 8288 1300
Fax (52) 81 8288 1301